

Front : Left

Actual	Before	Specified Range
-0.4°	-0.4°	-0.8° 0.2°
7.4°	7.4°	7.1° 8.1°
0.04°	0.19°*	-0.03° 0.18°
8.5°	8.6°	8.4° 9.4°
8.1°	8.1°	7.6° 9.6°

Camber
Caster
Toe
SAI
Included Angle
Turning Angle Diff.

Front : Right

Actual	Before	Specified Range
-0.5°	-0.5°	-0.8° 0.2°
7.1°	7.1°	7.1° 8.1°
0.05°	0.18°*	-0.03° 0.18°
8.5°	8.6°	8.4° 9.4°
8.1°	8.1°	7.6° 9.6°

Front

Cross Camber
Cross Caster
Cross SAI
Total Toe
Cross Turn Diff.

Actual	Before	Specified Range
0.1°	0.1°	-0.5° 0.5°
0.3°	0.3°	-0.5° 0.5°
0.0°	0.0°	
0.09°	0.37°*	-0.05° 0.35°

Rear : Left

Actual	Before	Specified Range
-1.2°	-1.2°	-1.3° -0.3°
0.09°	0.09°	-0.03° 0.17°

Camber
Toe

Rear : Right

Actual	Before	Specified Range
-1.3°*	-1.3°*	-1.3° -0.3°
0.09°	0.08°	-0.03° 0.17°

Rear

Cross Camber
Total Toe
Thrust Angle

Actual	Before	Specified Range
0.1°	0.1°	-0.5° 0.5°
0.18°	0.17°	-0.07° 0.33°
0.00°	0.00°	

-2-19-11

* This value is not within specification. Tire wear, handling and safety problems may result.