

# SCHEDULED MAINTENANCE LOG

## 6 Months or 5,000 Miles<sup>1</sup>

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 12 Months or 10,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

<sup>1</sup>This service is complimentary when performed by an authorized Lexus dealership.

## 18 Months or 15,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Clean air conditioner filter (RX)
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Visually inspect brake pads and rotors
- Road-test vehicle
- Inspect the following:
 

<input type="checkbox"/> Axle shaft boots	<input type="checkbox"/> Front differential oil (GX, LX)
<input type="checkbox"/> Ball joints and dust covers	<input type="checkbox"/> Rack and pinion assembly
<input type="checkbox"/> Body	<input type="checkbox"/> Rear differential oil (AWD/4WD only)
<input type="checkbox"/> Brake lines and hoses	<input type="checkbox"/> Steering linkage and boots
<input type="checkbox"/> Engine coolant (see page 68)	<input type="checkbox"/> Transfer case oil (RX AWD only)
<input type="checkbox"/> Exhaust pipes and mountings	

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### **Driving off-road, on dirt roads or on dusty roads:**

- Inspect engine air filter
- Tighten nuts and bolts on chassis

#### **Driving while towing:**

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (RX AWD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

# SCHEDULED MAINTENANCE LOG

## 24 Months or 20,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 30 Months or 25,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## SCHEDULED MAINTENANCE LOG

### 36 Months or 30,000 Miles

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace engine oil and oil filter; reset reminder light</li> <li><input type="checkbox"/> Rotate tires</li> <li><input type="checkbox"/> Lubricate axle shaft bushings (LX)</li> <li><input type="checkbox"/> Lubricate drive shaft, re-torque nuts and bolts (GX, LX)</li> <li><input type="checkbox"/> Replace air conditioner filter</li> <li><input type="checkbox"/> Inspect the following:             <ul style="list-style-type: none"> <li>___ Active height control system (LX)</li> <li>___ Axle shaft boots</li> <li>___ Ball joints and dust covers</li> <li>___ Body</li> <li>___ Brake lines and hoses</li> <li>___ Engine coolant (see page 68)</li> <li>___ Exhaust pipes and mountings</li> <li>___ Front differential oil (GX, LX)</li> <li>___ Fuel lines and connections, fuel tank band and fuel tank vapor vent system hoses</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace brake fluid</li> <li><input type="checkbox"/> Replace engine air filter</li> <li><input type="checkbox"/> Visually inspect brake pads and rotors</li> <li><input type="checkbox"/> Road-test vehicle</li> <li>___ Fuel tank cap gasket</li> <li>___ Rack and pinion assembly</li> <li>___ Rear differential oil (AWD/4WD only)</li> <li>___ Steering linkage and boots</li> <li>___ Transfer case oil (AWD/4WD only)</li> <li>___ Transmission fluid (RX)</li> <li>___ Transmission for signs of leakage (GX, LX)</li> </ul> |
|--|--|

#### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

##### **Driving off-road, on dirt roads or on dusty roads:**

- Tighten nuts and bolts on chassis

##### **Driving while towing:**

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (AWD/4WD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

# SCHEDULED MAINTENANCE LOG

## 42 Months or 35,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 48 Months or 40,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

**54 Months or 45,000 Miles**

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Clean air conditioner filter (RX)
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Visually inspect brake pads and rotors
- Road-test vehicle
- Inspect the following:
 

<input type="checkbox"/> Active height control system (LX)	<input type="checkbox"/> Exhaust pipes and mountings
<input type="checkbox"/> Axle shaft boots	<input type="checkbox"/> Front differential oil (GX, LX)
<input type="checkbox"/> Ball joints and dust covers	<input type="checkbox"/> Rack and pinion assembly
<input type="checkbox"/> Body	<input type="checkbox"/> Rear differential oil (AWD/4WD only)
<input type="checkbox"/> Brake lines and hoses	<input type="checkbox"/> Steering linkage and boots
<input type="checkbox"/> Engine coolant (see page 68)	<input type="checkbox"/> Transfer case oil (RX AWD only)

**Additional Maintenance Required If You Drive Primarily Under the Following Conditions**

**Driving off-road, on dirt roads or on dusty roads:**

- Inspect engine air filter
- Tighten nuts and bolts on chassis

**Driving while towing:**

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (RX AWD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

# SCHEDULED MAINTENANCE LOG

## 60 Months or 50,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 66 Months or 55,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 72 Months or 60,000 Miles

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace engine oil and oil filter; reset reminder light</li> <li><input type="checkbox"/> Rotate tires</li> <li><input type="checkbox"/> Lubricate axle shaft bushings (LX)</li> <li><input type="checkbox"/> Lubricate drive shaft, re-torque nuts and bolts (GX, LX)</li> <li><input type="checkbox"/> Replace active height control system fluid (LX)</li> <li><input type="checkbox"/> Replace air conditioner filter</li> <li><input type="checkbox"/> Inspect the following:             <ul style="list-style-type: none"> <li>___ Axle shaft boots</li> <li>___ Ball joints and dust covers</li> <li>___ Body</li> <li>___ Brake lines and hoses</li> <li>___ Charcoal canister (GX)<sup>1</sup></li> <li>___ Drive belt</li> <li>___ Engine coolant (see page 68)</li> <li>___ Engine valve clearance (GX)</li> <li>___ Exhaust pipes and mountings</li> <li>___ Front differential oil (GX, LX)</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace brake fluid</li> <li><input type="checkbox"/> Replace engine air filter</li> <li><input type="checkbox"/> Visually inspect brake pads and rotors</li> <li><input type="checkbox"/> Road-test vehicle</li> <li>___ Fuel lines and connections, fuel tank band and fuel tank vapor vent system hoses</li> <li>___ Fuel tank cap gasket</li> <li>___ Rack and pinion assembly</li> <li>___ Rear differential oil (AWD/4WD only)</li> <li>___ Steering linkage and boots</li> <li>___ Transfer case oil (AWD/4WD only)</li> <li>___ Transmission fluid (RX)</li> <li>___ Transmission for signs of leakage (GX, LX)</li> </ul> |
|--|--|

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### **Driving off-road, on dirt roads or on dusty roads:**

- Tighten nuts and bolts on chassis

#### **Driving while towing:**

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (AWD/4WD only)
- Replace transmission fluid
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:



# SCHEDULED MAINTENANCE LOG

## 78 Months or 65,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 84 Months or 70,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 90 Months or 75,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Clean air conditioner filter (RX)
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Visually inspect brake pads and rotors
- Road-test vehicle
- Inspect the following:
 

<ul style="list-style-type: none"> <li><input type="checkbox"/> Active height control system (LX)</li> <li><input type="checkbox"/> Axle shaft boots</li> <li><input type="checkbox"/> Ball joints and dust covers</li> <li><input type="checkbox"/> Body</li> <li><input type="checkbox"/> Brake lines and hoses</li> <li><input type="checkbox"/> Drive belt</li> <li><input type="checkbox"/> Engine coolant (see page 68)</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Exhaust pipes and mountings</li> <li><input type="checkbox"/> Front differential oil (GX, LX)</li> <li><input type="checkbox"/> Rack and pinion assembly</li> <li><input type="checkbox"/> Rear differential oil (AWD/4WD only)</li> <li><input type="checkbox"/> Steering linkage and boots</li> <li><input type="checkbox"/> Transfer case oil (RX AWD only)</li> </ul>
--	---

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect engine air filter
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (RX AWD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

# SCHEDULED MAINTENANCE LOG

## 96 Months or 80,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 102 Months or 85,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 108 Months or 90,000 Miles

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace engine oil and oil filter; reset reminder light</li> <li><input type="checkbox"/> Rotate tires</li> <li><input type="checkbox"/> Lubricate axle shaft bushings (LX)</li> <li><input type="checkbox"/> Lubricate drive shaft, re-torque nuts and bolts (GX, LX)</li> <li><input type="checkbox"/> Replace air conditioner filter</li> <li><input type="checkbox"/> Replace brake fluid</li> <li><input type="checkbox"/> Inspect the following:             <ul style="list-style-type: none"> <li>___ Active height control system (LX)</li> <li>___ Axle shaft boots</li> <li>___ Ball joints and dust covers</li> <li>___ Body</li> <li>___ Brake lines and hoses</li> <li>___ Drive belt</li> <li>___ Engine coolant (see page 68)</li> <li>___ Exhaust pipes and mountings</li> <li>___ Front differential oil (GX, LX)</li> <li>___ Fuel lines and connections, fuel tank band and fuel tank vapor vent system hoses</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace engine air filter</li> <li><input type="checkbox"/> Replace timing belt (GX)</li> <li><input type="checkbox"/> Visually inspect brake pads and rotors</li> <li><input type="checkbox"/> Road-test vehicle</li> <li>___ Fuel tank cap gasket</li> <li>___ Rack and pinion assembly</li> <li>___ Rear differential oil (AWD/4WD only)</li> <li>___ Steering linkage and boots</li> <li>___ Transfer case oil (AWD/4WD only)</li> <li>___ Transmission fluid (RX)</li> <li>___ Transmission for signs of leakage (GX, LX)</li> </ul> |
|--|---|

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### **Driving off-road, on dirt roads or on dusty roads:**

- Tighten nuts and bolts on chassis

#### **Driving while towing:**

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (AWD/4WD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

# SCHEDULED MAINTENANCE LOG

## 114 Months or 95,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 120 Months or 100,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Replace engine coolant (see page 68)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 126 Months or 105,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Clean air conditioner filter (RX)
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Visually inspect brake pads and rotors
- Road-test vehicle
- Inspect the following:
 

<input type="checkbox"/> Active height control system (LX)	<input type="checkbox"/> Exhaust pipes and mountings
<input type="checkbox"/> Axle shaft boots	<input type="checkbox"/> Front differential oil (GX, LX)
<input type="checkbox"/> Ball joints and dust covers	<input type="checkbox"/> Rack and pinion assembly
<input type="checkbox"/> Body	<input type="checkbox"/> Rear differential oil (AWD/4WD only)
<input type="checkbox"/> Brake lines and hoses	<input type="checkbox"/> Steering linkage and boots
<input type="checkbox"/> Drive belt	<input type="checkbox"/> Transfer case oil (RX AWD only)

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### **Driving off-road, on dirt roads or on dusty roads:**

- Inspect engine air filter
- Tighten nuts and bolts on chassis

#### **Driving while towing:**

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (RX AWD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

# SCHEDULED MAINTENANCE LOG

## 132 Months or 110,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 138 Months or 115,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Inspect engine coolant (see page 68)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## SCHEDULED MAINTENANCE LOG

### 144 Months or 120,000 Miles

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace engine oil and oil filter; reset reminder light</li> <li><input type="checkbox"/> Rotate tires</li> <li><input type="checkbox"/> Lubricate axle shaft bushings (LX)</li> <li><input type="checkbox"/> Lubricate drive shaft, re-torque nuts and bolts (GX, LX)</li> <li><input type="checkbox"/> Replace active height control system fluid (LX)</li> <li><input type="checkbox"/> Replace air conditioner filter</li> <li><input type="checkbox"/> Inspect the following:             <ul style="list-style-type: none"> <li>___ Axle shaft boots</li> <li>___ Ball joints and dust covers</li> <li>___ Body</li> <li>___ Brake lines and hoses</li> <li>___ Charcoal canister<sup>2</sup></li> <li>___ Drive belt</li> <li>___ Engine valve clearance (GX)</li> <li>___ Exhaust pipes and mountings</li> <li>___ Front differential oil (GX, LX)</li> <li>___ Fuel lines and connections, fuel tank band and fuel tank vapor vent system hoses</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace brake fluid</li> <li><input type="checkbox"/> Replace engine air filter</li> <li><input type="checkbox"/> Replace spark plugs<sup>1</sup> (for RX, use Denso FK20HR11 plugs or equivalent)</li> <li><input type="checkbox"/> Visually inspect brake pads and rotors</li> <li><input type="checkbox"/> Road-test vehicle</li> <li>___ Fuel tank cap gasket</li> <li>___ Rack and pinion assembly</li> <li>___ Rear differential oil (AWD/4WD only)</li> <li>___ Steering linkage and boots</li> <li>___ Transfer case oil (AWD/4WD only)</li> <li>___ Transmission fluid (RX)</li> <li>___ Transmission for signs of leakage (GX, LX)</li> </ul> |
|---|---|

#### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

##### Driving off-road, on dirt roads or on dusty roads:

- Tighten nuts and bolts on chassis

##### Driving while towing:

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (AWD/4WD only)
- Replace transmission fluid
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

<sup>1</sup>Required under the terms of the Emission Control Warranty.

<sup>2</sup>Required only for vehicles in California, Massachusetts and New York.



# SCHEDULED MAINTENANCE LOG

## 150 Months or 125,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 156 Months or 130,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Inspect engine coolant (see page 68)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 162 Months or 135,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Clean air conditioner filter (RX)
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Visually inspect brake pads and rotors
- Road-test vehicle
- Inspect the following:
 

<input type="checkbox"/> Active height control system (LX)	<input type="checkbox"/> Exhaust pipes and mountings
<input type="checkbox"/> Axle shaft boots	<input type="checkbox"/> Front differential oil (GX, LX)
<input type="checkbox"/> Ball joints and dust covers	<input type="checkbox"/> Rack and pinion assembly
<input type="checkbox"/> Body	<input type="checkbox"/> Rear differential oil (AWD/4WD only)
<input type="checkbox"/> Brake lines and hoses	<input type="checkbox"/> Steering linkage and boots
<input type="checkbox"/> Drive belt	<input type="checkbox"/> Transfer case oil (RX AWD only)

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### **Driving off-road, on dirt roads or on dusty roads:**

- Inspect engine air filter
- Tighten nuts and bolts on chassis

#### **Driving while towing:**

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (RX AWD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

# SCHEDULED MAINTENANCE LOG

## 168 Months or 140,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Replace air conditioner filter (LX)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 174 Months or 145,000 Miles

- Replace engine oil and oil filter; reset reminder light
- Rotate tires
- Inspect engine coolant (see page 68)
- Visually inspect brake pads and rotors
- Road-test vehicle

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Inspect axle shaft boots
- Inspect ball joints and dust covers
- Inspect engine air filter
- Inspect steering linkage and boots
- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

#### Driving while towing:

- Lubricate drive shaft, re-torque nuts and bolts (GX, LX)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

## 180 Months or 150,000 Miles

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace engine oil and oil filter; reset reminder light</li> <li><input type="checkbox"/> Rotate tires</li> <li><input type="checkbox"/> Lubricate axle shaft bushings (LX)</li> <li><input type="checkbox"/> Lubricate drive shaft, re-torque nuts and bolts (GX, LX)</li> <li><input type="checkbox"/> Replace air conditioner filter</li> <li><input type="checkbox"/> Inspect the following:             <ul style="list-style-type: none"> <li>___ Active height control system (LX)</li> <li>___ Axle shaft boots</li> <li>___ Ball joints and dust covers</li> <li>___ Body</li> <li>___ Brake lines and hoses</li> <li>___ Drive belt</li> <li>___ Exhaust pipes and mountings</li> <li>___ Front differential oil (GX, LX)</li> <li>___ Fuel lines and connections, fuel tank band and fuel tank vapor vent system hoses</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Replace brake fluid</li> <li><input type="checkbox"/> Replace engine air filter</li> <li><input type="checkbox"/> Replace engine coolant (see page 68)</li> <li><input type="checkbox"/> Visually inspect brake pads and rotors</li> <li><input type="checkbox"/> Road-test vehicle</li> <li>___ Fuel tank cap gasket</li> <li>___ Rack and pinion assembly</li> <li>___ Rear differential oil (AWD/4WD only)</li> <li>___ Steering linkage and boots</li> <li>___ Transfer case oil (AWD/4WD only)</li> <li>___ Transmission fluid (RX)</li> <li>___ Transmission for signs of leakage (GX, LX)</li> </ul> |
|--|---|

### Additional Maintenance Required If You Drive Primarily Under the Following Conditions

#### Driving off-road, on dirt roads or on dusty roads:

- Tighten nuts and bolts on chassis

#### Driving while towing:

- Replace front differential oil (GX, LX)
- Replace rear differential oil (AWD/4WD only)
- Replace transfer case oil (AWD/4WD only)
- Tighten nuts and bolts on chassis

Date: \_\_\_\_\_ Mileage: \_\_\_\_\_

Notes:

The following descriptions are provided to give you a better understanding of the maintenance services that should be performed on your vehicle. The scheduled maintenance log indicates at which time/mileage intervals each service should be performed. Please note that many maintenance services should be performed only by a qualified technician.

For further information on maintenance services that you can perform yourself, see the maintenance sections of your *Owner's Manual*.

### **Active Height Control System**

Inspect the lines, accumulators and pump and replace the system fluid when specified. For recommended fluid, refer to your *Owner's Manual*.

### **Air Conditioner Filter**

Clean or replace at specified intervals. More frequent cleaning or replacement may be required when driving in dusty conditions. Refer to your *Owner's Manual* for service details.

### **Axle Shaft Boots**

Check the axle shaft boots and clamps for cracks, deterioration and damage. Replace any damaged parts and, if necessary, repack the grease. A qualified technician should perform these operations.

### **Axle Shaft Bushings**

Repack the front axle shaft bushings with molybdenum-disulfide lithium-base chassis grease. A qualified technician should perform this operation.

### **Ball Joints and Dust Covers**

Check the suspension and steering linkage ball joints for looseness and damage. Check all dust covers for deterioration and damage. A qualified technician should perform these inspections.

### **Body Inspection**

Visually check for corrosion, scratches and other damage. Check outer body panels, inner panels of the hood and doors, and underneath the vehicle. Apply touch-up paint to any chips and scratches or have them repaired by a qualified technician.

### Brake Fluid

Replace using fluid type specified in your *Owner's Manual*. A qualified technician should perform this operation.

### Brake Lines and Hoses

Visually inspect for proper installation. Check for chafing, cracks, deterioration and signs of leakage. Replace any deteriorated or damaged parts. A qualified technician should perform these operations.

### Brake Pads/Rotors and Parking Brake Linings/Drums

Check brake pads and rotors for excessive wear; check brake rotors for runout. Check brake calipers for fluid leakage. Check the parking brake linings (shoes) and drums for scoring, burning, fluid leakage, broken parts and excessive wear. A qualified technician should perform these inspections.

### Charcoal Canister

Check for internal damage and clogging. If necessary, clean with compressed air or replace. A qualified technician should perform these operations.

### Differential Oil

Check for correct oil level and inspect each differential component for signs of leakage. If you discover any leakage, have it repaired immediately by a qualified technician. Refer to your *Owner's Manual* for fluid specifications.

### Drive Belt

Inspect for cracks, excessive wear and oiliness. Check the belt tension and adjust if necessary. Replace the belts if they are damaged.

### Drive Shaft

Lubricate the drive shaft spiders and slide yokes with lithium-base chassis grease and the double cardan joint with molybdenum-disulfide lithium-base chassis grease, and re-torque the flange nuts and bolts. Only a qualified technician should re-torque the flange nuts and bolts. If vehicle is submerged, lubricate within 24 hours, regardless of maintenance interval.

### Engine Air Filter

Check for damage, excessive wear and oiliness. Replace if necessary.

### Engine Coolant

When inspecting, visually check the engine coolant level on the see-through reservoir. Add coolant as necessary. When replacing, drain and flush the cooling system and refill with coolant. Always use Genuine Toyota Super Long-Life Coolant or similar high-quality non-silicate, non-amine, non-borate ethylene-glycol coolant with long-life hybrid organic acid technology (i.e., a combination of low phosphates and organic acids). A qualified technician should perform these operations.

**Note:** Initial replacement is at 120 months/100,000 miles. Replace every 60 months/50,000 miles thereafter.

### Engine Oil and Oil Filter

Replace the oil filter and drain and refill the engine oil at specified intervals. For recommended oil grade and viscosity, refer to your *Owner's Manual*. Some models are equipped with a replaceable oil-filter element and oil-filter cap O-ring; replace both at each oil change. For instructions on how to reset the reminder light, refer to your *Owner's Manual*.

### Engine Valve Clearance (GX)

Inspect for excessive lifter noise and engine vibration and adjust if necessary. A qualified technician should perform this operation. (The LX 570 and RX 350 are equipped with hydraulic valve lash adjusters that require no periodic clearance inspection or adjustment.)

### Exhaust Pipes and Mountings

Visually inspect the exhaust pipes, muffler and hangers for cracks, deterioration and damage. Start the engine and listen carefully for any exhaust leakage. Tighten connections and replace parts as necessary.

### Fuel Lines and Connections, Fuel Tank Band and Fuel Tank Vapor Vent System Hoses

Visually inspect for corrosion, damage, cracks, and loose or leaking connections. Tighten connections and replace parts as necessary.

### Fuel Tank Cap Gasket

Visually inspect for cracks, deterioration and damage and replace if necessary.

### Nuts and Bolts on Chassis

Check that tightness of the seat-mounting bolts and front/rear suspension-member retaining bolts matches torque measurements specified in the *Repair Manual*.

### Rack and Pinion Assembly

Inspect the rack and pinion assembly for signs of leakage, damage and loose electrical connections. Tighten connections and if you discover any leakage or damage, have it repaired immediately by a qualified technician.

### Road Test

While driving the vehicle, check for proper operation of engine, transmission, brakes and steering. Also check for abnormal noise or vibration from any part of the vehicle.

### Spark Plugs

Replace at specified interval. Install new plugs of the same type as originally equipped (see your *Owner's Manual*). A qualified technician should perform this operation. To ensure optimum engine performance on RX 350, replace only with Denso FK20HR11 plugs or equivalent.

### Steering Linkage and Boots

With the vehicle stopped, check for excessive freeplay in the steering wheel. Inspect the linkage for bending and damage and the dust boots for deterioration, cracks and damage. Replace any damaged parts. A qualified technician should perform these operations.

### Timing Belt (GX)

Replace every 108 months or 90,000 miles. A qualified technician should perform this operation.

### Timing Chain (LX, RX)

The LX 570 and RX 350 are equipped with a timing chain that requires no periodic inspection.

### Tire Rotation

Tires should be rotated according to the instructions in your *Owner's Manual*. When rotating tires, check pressure and check for damage and uneven wear. If the spare is not rotated, check the condition and pressure of the spare.



### Transfer Case Oil

Check for correct oil level and inspect each component for signs of leakage. If you discover any leakage, have it repaired immediately by a qualified technician. For correct oil, refer to your *Owner's Manual*.

### Transmission (GX, LX)

On GX 470 and LX 570, the transmission and transmission fluid are a completely sealed unit. Therefore, periodic checks and replacement of the transmission fluid are not required, and there is no dipstick on the transmission. Any repairs that require adding or replacing fluid should be performed by a qualified technician following procedures in Lexus service and repair publications.

### Transmission Fluid (RX)

Check for correct fluid level and inspect each transmission component for signs of leakage. If you discover any leakage, have it repaired immediately by a qualified technician.