


TERMINALS OF ECU



R04656

Symbols (Terminals No.)	Wiring Color	Condition	STD Voltage (V)
STP (A12 - 1) - GND (A14 - 26)	L-B ↔ W-B	IG switch ON, brake pedal is released	0 - 1.2
		IG switch ON, brake pedal is depressed	9 - 14
REG (A12 - 3) - GND (A14 - 26)	P ↔ W-B	IG switch ON	0 - 1.2
		Engine idling	9 - 14
HSW (A12 - 5) - GND (A14 - 26)	LG ↔ W-B	IG switch ON, height control switch "NORM"	9 - 14
		IG switch ON, height control switch "HIGH"	0 - 1.2
T _D (A12 - 6) - GND (A14 - 26)	GR ↔ W-B	IG switch ON, connect between terminals T _D and E1 of DLC2	0 - 1.2
		IG switch ON, disconnect between terminals T _D and E1 of DLC2	9 - 14
VH (A12 - 7) - GND (A14 - 26)	V-R ↔ W-B	IG switch ON, height control switch "NORM"	0 - 1.2
		IG switch ON, height control switch "HIGH"	9 - 14
SS2 (A12 - 8) - GND (A14 - 26)	LG-R ↔ W-B	IG switch ON, steering wheel is being turned slowly	Repeat 0 ↔ Approx. 5
SS1 (A12 - 9) - GND (A14 - 26)	V ↔ W-B	IG switch ON, steering wheel is being turned slowly	Repeat 0 ↔ Approx. 5
DOOR (A12 - 10) - GND (A14 - 26)	R-W ↔ W-B	IG switch ON, each door opened	0 - 1.2
		IG switch ON, all door closed	9 - 14
T _c (A12 - 11) - GND (A14 - 26)	LG-B ↔ W-B	IG switch ON, connect between terminals T _c and E1 of DLC2	0 - 1.2
		IG switch ON, disconnect between terminals T _c and E1 of DLC2	9 - 14
T _s (A12 - 12) - GND (A14 - 26)	G ↔ W-B	IG switch ON, connect between terminals T _s and E1 of DLC2	0 - 1.2
		IG switch ON, disconnect between terminals T _s and E1 of DLC2	9 - 14
L1 (A13 - 1) - GND (A14 - 26)	V-Y ↔ W-B	IG switch ON, engine running, shift position N → D	N → D 5 → 0 → 5
SHRL (A13 - 2) - GND (A14 - 26)	W-G ↔ W-B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	NORM ↔ HIGH Approx. 2.5 ↔ 2.7
SHRR (A13 - 3) - GND (A14 - 26)	B ↔ W-B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	NORM ↔ HIGH Approx. 2.5 ↔ 2.7
SGFL (A13 - 9) - GND (A14 - 26)	P ↔ W-B	IG switch ON, keep the vehicle still without any vertical movement for 1 second	Approx. 2.5
SHFL (A13 - 10) - GND (A14 - 26)	V ↔ W-B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	NORM ↔ HIGH Approx. 2.5 ↔ 2.7
SHFR (A13 - 11) - GND (A14 - 26)	V-R ↔ W-B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	NORM ↔ HIGH Approx. 2.5 ↔ 2.7
SGL (A13 - 12) - GND (A14 - 26)	LG-B ↔ W-B	Always	Continuity (Ω)
SGRR (A14 - 6) - GND (A14 - 26)	O ↔ W-B	IG switch on, keep the vehicle still without any vertical movement for 1 second	NORM ↔ HIGH Approx. 2.5 ↔ 2.7

Symbols (Terminals No.)	Wiring Color	Condition	STD Voltage (V)
SGR (A14 – 7) – GND (A14 – 26)	BR–R ↔ W–B	IG switch ON	Approx. 5
RM+ (A14 – 8) – GND (A14 – 26)	R–L ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	0 – 1
RC (A14 – 9) – GND (A14 – 26)	G–Y ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	9 – 14
SLFR (A14 – 10) – GND (A14 – 26)	R–B ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	9 – 14
SLRR (A14 – 11) – GND (A14 – 26)	P–L ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	9 – 14
BAT (A14 – 12) – GND (A14 – 26)	R ↔ W–B	Always	9 – 14
+B (A14 – 13) – GND (A14 – 26)	W–R ↔ W–B	IG switch ON	9 – 14
SGFR (A14 – 19) – GND (A14 – 26)	V ↔ W–B	IG switch ON, keep the vehicle still without any vertical movement for 1 second	Approx. 2.5
RM– (A14 – 21) – GND (A14 – 26)	BR–Y ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	0 – 1
SLEX (A14 – 22) – GND (A14 – 26)	V–Y ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	9 – 14
SLFL (A14 – 23) – GND (A14 – 26)	R–W ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	9 – 14
SLRL (A14 – 24) – GND (A14 – 26)	P ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	9 – 14
SLRR (A14 – 11) – GND (A14 – 26)	P–L ↔ W–B	Engine idling, height control switch from "NORM" to "HIGH" or reverse	9 – 14
GND (A14 – 26) – Body ground	W–B ↔ Body	Always	Continuity (Ω)